

Revision Date: 06/05/2006

Issue date: 06/05/2006

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: Silver Grade Anti-Seize Lubricant
Product type: Lubricant
Company address:
Henkel Corporation
1001 Trout Brook Crossing
Rocky Hill, Connecticut 06067

Item No. : 76764
Region: United States
Contact Information:
Telephone: 860.571.5100
Emergency telephone: 860.571.5100
Internet: www.loctite.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

| <u>Hazardous components</u> | <u>%</u> | <u>ACGIH TLV</u> | <u>OSHA PEL</u> | <u>OTHER</u> |
|----------------------------------------------------------------------|----------|-------------------------------------------------------------------------------|---------------------------------------------------------------------|--------------|
| Distillates (petroleum), hydrotreated heavy naphthenic 64742-52-5 | 30-60 | 5 mg/m ³ TWA (mist) 10mg/m ³ STEL (mist) | 5 mg/m ³ TWA (mist) | None |
| Graphite 7782-42-5 | 10-30 | 2 mg/m ³ TWA respirable fraction, all forms except graphite fibers | 15 mg/m ³ (total), 5 mg/m ³ (respirable) | None |
| Calcium oxide 1305-78-8 | 10-30 | 2 mg/m ³ TWA | 5 mg/m ³ (TWA) | None |
| Distillates (petroleum), hydrotreated light naphthenic 64742-53-6 | 10-30 | 5 mg/m ³ TWA (mist) 10mg/m ³ STEL (mist) | 5 mg/m ³ TWA (mist) | None |
| Aluminum 7429-90-5 | 5-10 | 10 mg/m ³ TWA metal dust 5 mg/m ³ TWA as Al | 15 mg/m ³ TWA (total), 5 mg/m ³ (respirable) | None |
| Distillates (petroleum), straight-run middle 64741-44-2 | 1-5 | 5 mg/m ³ TWA (mist) 10mg/m ³ STEL (mist) | 5 mg/m ³ mist | None |
| Silica, quartz 14808-60-7 | 0.1-1 | 0.05 mg/m ³ TWA respirable fraction | 0.1mg/m ³ TWA (respirable) | None |

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HMIS:

Physical state: Paste
Color: Silver
Odor: Hydrocarbon-like

HEALTH: 1
FLAMMABILITY: 1
PHYSICAL HAZARD: 1
Personal Protection: See Section 8

WARNING: CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects

Inhalation: Moderate respiratory tract irritation.
Skin contact: Moderate skin irritation.
Eye contact: Moderate eye irritation.

Item No. : 76764

Product name: Silver Grade Anti-Seize Lubricant

Ingestion: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Principal hazard of ingestion is aspiration into the lungs and subsequent pneumonitis.

Existing conditions aggravated by exposure: Eye, skin, and respiratory disorders.

See Section 11 for additional toxicological information.

4. FIRST AID MEASURES

Inhalation: Remove to fresh air. If discomfort persists seek medical attention.

Skin contact: Wash with soap and water. If symptoms persist, obtain medical attention.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.

Ingestion: Do not induce vomiting. Get medical attention immediately.

5. FIRE-FIGHTING MEASURES

Flash point: >93°C (>200°F)

Autoignition temperature: Not determined

Flammable/Explosive limits-lower %: Not available

Flammable/Explosive limits-upper %: Not available

Extinguishing media: Carbon dioxide (CO₂). Foam. Dry chemical.

Special fire fighting procedures: None

Unusual fire or explosion hazards: None

Hazardous combustion products: Oxides of carbon. Oxides of nitrogen.

6. ACCIDENTAL RELEASE MEASURES

Environmental precautions: Prevent further leakage or spillage.

Clean-up methods: Remove all ignition sources. Soak up with inert absorbent. Store in a closed container until ready for disposal.

7. HANDLING AND STORAGE

Handling: Keep away from heat, spark and flame. Avoid contact with skin and eyes.

Storage: Keep in a cool, well ventilated area.

Incompatible products: No special restrictions on storage with other products.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering controls: Use local ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Item No. : 76764

Product name: Silver Grade Anti-Seize Lubricant

Skin protection: Neoprene or oil resistant gloves

Eye/face protection: Safety goggles or safety glasses with side shields.

See Section 2 for exposure limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Paste
Color: Silver
Odor: Hydrocarbon-like
Vapor pressure: <5 mmHg @20°C (68° F)
pH: Not applicable
Boiling point/range: Not available
Melting point/range: Not available
Specific gravity: 1.25
Vapor density: Not available
Evaporation rate: Not available
Solubility in water: Insoluble
Partition coefficient (n-octanol/water): Not determined
VOC content: 12.96%; 162 grams/liter

10. STABILITY AND REACTIVITY

Stability: Stable.
Hazardous polymerization: Will not occur.
Hazardous decomposition products: None reasonably foreseeable
Incompatibility: Strong oxidizing agents.
Conditions to avoid: None known.

11. TOXICOLOGICAL INFORMATION

Carcinogen Status

| Hazardous components | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen |
|----------------------------------------------------------------------|-----------------------|------------------------|------------------------|
| Distillates (petroleum), hydrotreated heavy naphthenic 64742-52-5 | No | No | No |
| Graphite 7782-42-5 | No | No | No |
| Calcium oxide 1305-78-8 | No | No | No |
| Distillates (petroleum), hydrotreated light naphthenic 64742-53-6 | No | No | No |
| Aluminum 7429-90-5 | No | No | No |
| Distillates (petroleum), straight-run middle 64741-44-2 | No | No | No |
| Silica, quartz 14808-60-7 | Known Carcinogen | Group 1 | Yes |

Literature Referenced Target Organ & Other Health Effects

| Hazardous components | Health Effects/Target Organs |
|----------------------------------------------------------------------|-------------------------------------------------------|
| Distillates (petroleum), hydrotreated heavy naphthenic 64742-52-5 | Irritant |
| Graphite 7782-42-5 | Lung |
| Calcium oxide 1305-78-8 | Irritant, Eyes, Corrosive |
| Distillates (petroleum), hydrotreated light naphthenic 64742-53-6 | Irritant |
| Aluminum 7429-90-5 | Central nervous system, Irritant, Lung |
| Distillates (petroleum), straight-run middle 64741-44-2 | Irritant |
| Silica, quartz 14808-60-7 | Some evidence of carcinogenicity, Lung, Immune system |

12. ECOLOGICAL INFORMATION

Ecological information: Not available

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

EPA hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR):

Proper shipping name: Unrestricted
Hazard class or division: None
Identification number: None
Packing group: None

International Air Transportation (ICAO/IATA):

Proper shipping name: Unrestricted
Hazard class or division: None
Identification number: None
Packing group: None

Water Transportation (IMO/IMDG):

Proper shipping name: Unrestricted
Hazard class or division: None
Identification number: None
Packing group: None
Marine pollutant: None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12 (b) Export Notification: None.

CERCLA/SARA Section 302 EHS: None.
CERCLA/SARA Section 311/312: Immediate Health Hazard
CERCLA/SARA 313: Aluminum (CAS# 7429-90-5) (dust and fumes only).

California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Domestic Substances List.
WHMIS hazard class: D.2.A, D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New information added in section(s): 2

Prepared by: C.J. Michaels, Senior Product Safety & Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.