

MATERIAL SAFETY DATA SHEET

SPOTCHECK® CLEANER/REMOVER SKC-S

1. IDENTIFICATION

Company: MAGNAFLUX

Address: 3624 West Lake Avenue, Glenview, Illinois 60026

Telephone No.: 847-657-5300 (Off-Hour Emergency Number - CHEMTREC - 1-800-424-9300).

Product Use: Wipe on solvent cleaner/remover for penetrant inspection Packages: 1 gallon can, 5 gallon pail, 55 gallon drums, aerosols

NFPA Rating: Health 1, Flammability 3, Reactivity 0

PIN (Canada): Bulk: UN1268 Revision Date: April 13, 2007

2. HAZARDOUS INGREDIENTS

<u>Ingredient</u>	Wt./Wt. %	CAS#	<u>TLV</u>	<u>PEL</u>	<u>LD₅₀</u>	<u>LC₅₀</u>
			300ppm		5 g/kg	3400 ppm
Light aliphatic solvent naphtha	60-100	64742-89-8	(8 hr.TWA)	not avail.	(oral/rat)	(4hrs/rat)
Carbon dioxide propellant (Aerosol Only)	3-7	124-38-9	not avail.	5000 ppm	not avail.	not avail.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Flammable liquid and aerosol. Vapor may cause flash fire. Harmful or fatal if swallowed. Mist or vapor may irritate the respiratory tract. Liquid contact may cause eye and skin irritation. Over-exposure may cause central nervous system (CNS) depression and target organ effects. Spills may create a slipping hazard.

POTENTIAL HEALTH EFFECTS & SIGNS AND SYMPTOMS OF EXPOSURE:

Skin Contact: Irritating to skin. Repeated exposure may cause skin dryness or cracking.

Eyes: Vapors may be irritating to the eye.

Inhalation: Vapors expected to be slightly irritating. Vapors may cause drowsiness and dizziness.

Ingestion: Harmful: may cause lung damage if swallowed.

Medical conditions known to be aggravated by exposure to product: Pre-existing medical conditions of the following organ(s) or organ

system(s) may be aggravated by exposure to this material: Eyes, Skin, Respiratory system.

FIRST AID

Skin Contact: Wash off with soap and water. Use soothing lotion.

Eyes: Rinse carefully under upper and lower eyelids using plenty of water. Rest eyes for 30 minutes. If redness, burning,

blurred vision, or swelling persist, transport to the nearest medical facility for additional treatment.

Inhalation: Remove to fresh air if dizzy or nauseated. If rapid recovery does not occur, transport to nearest medical facility for

additional treatment.

Ingestion: Do not induce vomiting. Transport to nearest medical facility for additional treatment. If vomiting occurs

spontaneously, keep head below hips to prevent aspiration.

NOTE: In all severe cases, contact physician immediately. Local telephone operators can furnish number of regional poison control center.

5. FIRE HAZARD

Conditions of flammability: Bulk and aerosol: Readily ignited in presence of ignition sources.

Flash point: Min. 57°F (14°C) (Pensky-Martens) closed cup.

Flammable limits in air: 1% to 6%.

Extinguishing media: Carbon dioxide, foam

Special fire fighting procedures: Keep containers cool with water spray. Do not spray water directly on burning SKC-S. It will

float and spread the fire.

Hazardous combustion products: Smoke, soot, oxides of carbon.

Unusual fire hazards: Aerosol cans may burst if heated above 130°F (54°C) and spray contents into a fire.

6. ACCIDENTAL RELEASE MEASURES

Mop up or sweep up with absorbent. Avoid contact with spilled or released material. Immediately remove all contaminated clothing. (For disposal, see Section 13.)

7. HANDLING AND STORAGE

Avoid eye contact. Avoid repeated or prolonged skin contact. Avoid breathing spray mist. Do not spray near arcs or flames. Use only in well ventilated areas. Wash thoroughly after handling.



A Division of Illinois Tool Works Inc.

3624 WEST LAKE AVENUE ■ GLENVIEW, ILLINOIS 60026

TEL 847.657.5300 FAX 847.657.5388

SPOTCHECK®

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Controls: Use where ventilation will carry spray mist away from occupied areas.

Personal protection: Wear safety glasses to protect eyes. Wear nitrile rubber gloves if hand exposure is unavoidable.

Respirator with solvent vapor absorbing cartridge if used in enclosed, unventilated space.

9. PHYSICAL PROPERTIES

Initial boiling point (bulk): Min. 245°F (118°C) (ASTM D-86) Vapor pressure: 12 and 16 oz.Aerosol: 105psi @ 75°F(24°C)

Bulk: 1.5 - 2.0 kPa at 68.0°F

4.1

Fast

VOC Content (EPA Method 24):750 g/LVapor density:Density/sp. gravity:0.76Evaporation rate:

Water solubility: 0 Appearance: Clear, colorless liquid

pH: Neutral Odor: Naphtha odor

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of use

Incompatibility: Avoid heat, sparks, open flames and other ignition sources. Avoid strong oxidizing agents. Hazardous decomposition products: A complex mixture of airborne solids, liquids, and gases, including carbon monoxide, carbon

dioxide and other organic compounds will be evolved when this material undergoes combustion

or thermal or oxidative degradation.

Reactivity: None

11. TOXICOLOGICAL INFORMATION

Carcinogenicity: Contains no known or suspected carcinogens listed with OSHA, IARC, NTP, or ACGIH.

Threshold limit value: 300 ppr

WHMIS information (Canada): According to available information, the ingredients have not been found to show reproductive

toxicity, teratogenicity, mutagenicity, skin sensitization, or synergistic toxic effects with other

materials.

12. **ECOLOGICAL INFORMATION**

No data is available on SKC-S. It floats on water and evaporates away. It is 100% VOC.

13. DISPOSAL

As hazardous waste, send to licensed waste handler who can blend it into secondary fuels.

RCRA: Hazardous waste.

U.S. EPA Waste Number: D001

14. TRANSPORTATION

U.S. DOT: 49 CFR 172.101 Hazardous Materials Table

Non-Aerosol Aerosol

Proper shipping name: Petroleum distillates, n.o.s. Consumer Commodity

Hazard class or division:

Identification No.:

UN1268

None
Packing Group:

II

None

IATA: List of Dangerous Goods Non-Aerosol Aerosol

Proper shipping name: Petroleum distillates, n.o.s. Aerosols, flammable

Hazard class or division:32.1Identification No.:UN1268UN1950

Packing Group:

 IMDG: General Index
 Non-Aerosol
 Aerosol

 Proper shipping name:
 PETROLEUM DISTILLATES,N.O.S.
 AEROSOLS

Hazard class of division:3.22.1Identification No.:UN1268UN1950Packing Group:II-



SPOTCHECK®

REGULATORY INFORMATION

TSCA: All ingredients are listed in TSCA inventory. Canadian DSL: All ingredients are listed in the Canadian DSL

VM&P Naphtha (64742-89-8) Reportable Quantity 66,667 lbs. CERCLA: SARA TITLE III, Section 313:

Xylene, Mixed Isomer (1330-20-7) <0.13%; meta-Xylene (108-38-3)< 0.05%; Ethylbenzene

(100-41-4)< 0.03%; Benzene (71-43-2) < 0.005%; Toluene (108-88-3) < 0.01%

California Proposition 65: Warning: This material may contain trace amounts of chemicals known to the state of California

to cause cancer and/or birth defects and/or reproductive harm.

Non-Aerosol: B-2, D-2B; Aerosol: A, B-5, D-2B WHMIS Class (Canada):

Note: This MSDS has been prepared to meet WHMIS (Canada) requirements with the exception of using 16 headings.

OTHER INFORMATION

Revision Statement: Section 9 October 26, 2004 Supersedes:

Prepared by: Tamie Simmons, Research Manager

