

## MATERIAL SAFETY DATA SHEET

MSDS 0463

## Section 1 -- PRODUCT AND COMPANY

## IDENTIFICATION

		HMIS CODES	
PRODUCT NAME		Health	1
Metacaulk 835+		Flammability	0
		Reactivity	0
PRODUCT CODES		PPI	B
66012, 66019			
CHEMICAL FAMILY:			
Organic/Inorganic			
USE			
Firestopping Sealant			
MANUFACTURER'S NAME		EMERGENCY TELEPHONE NO.	
The RectorSeal Corporation		Chemtrec 24 Hours	
2601 Spenwick Drive		(800) 424-9300	
Houston, Texas 77055 USA			
DATE OF PREPARATION		TECHNICAL SERVICE TELEPHONE NO.	
July 24, 2002		(800) 231-3345	

## Section 2 -- COMPOSITION/INFORMATION ON INGREDIENTS

% by WT	CAS No.	INGREDIENT	UNITS
3-7	7631-86-9	Amorphous Silica	
		ACGIH TLV	N/D ppm
		OSHA PEL	N/D ppm
3-7	22984-54-9	Ketoxime Silane	
		ACGIH TLV	N/D ppm
		OSHA PEL	N/D ppm
15-40	1317-65-3	Calcium Carbonate	
		ACGIH TLV	10 mg/m3
		OSHA PEL	15 mg/m3

## Section 3 -- HAZARDS IDENTIFICATION

## SUMMARY OF ACUTE HAZARDS

May cause skin irritation.

## ROUTE OF EXPOSURE, SIGNS AND SYMPTOMS

## INHALATION

Not a respiratory irritant.

## EYE CONTACT

Contact may cause eye irritation.

## SKIN CONTACT

Contact may cause skin irritation.

INGESTION

Possible irritation to mucous membranes of the mouth, throat, and stomach.

SUMMARY OF CHRONIC HAZARDS

None known.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Persons with pre-existing skin conditions or chemical allergies may be more

susceptible to contact effects of the cured elastomer.

Section 4 -- FIRST AID MEASURES

- If INHALED: Not a respiratory irritant.
- If on SKIN: Wash with soap and water. If irritation occurs, seek medical attention.
- If in EYES: Immediately flush with large amounts of water. If irritation occurs, seek medical attention.
- If SWALLOWED: If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person.

Section 5 -- FIRE FIGHTING MEASURES

FLASH POINT	LEL	UEL
None	N/D	N/D

EXTINGUISHING MEDIA

Foam, dry chemical, carbon dioxide or water fog.

SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus (SCBA) and other protective clothing. Hazardous decomposition products possible (see Section 10).

UNUSUAL FIRE AND EXPLOSION HAZARDS: Heat may build up and rupture closed containers.

Section 6 -- ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Wipe up spills to prevent footing hazard. Avoid flushing into sewers, drains, waterways and soil. Wear protective clothing during clean up.

Section 7 -- HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Keep container closed and upright when not in use. To prevent freezing and possible rupture of container, do not store below 40 F.

OTHER PRECAUTIONS: Avoid prolonged or repeated contact with skin or clothing. Empty containers may contain residues and vapors; treat as if full and observe all product precautions. Do not reuse empty containers. KEEP OUT OF REACH OF CHILDREN.

=====  
Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION  
-----

RESPIRATORY PROTECTION (SPECIFY TYPE): None required.  
VENTILATION - LOCAL EXHAUST: Acceptable  
SPECIAL: N/A  
MECHANICAL (GENERAL): Preferable  
OTHER: N/A  
PROTECTIVE GLOVES: Wear rubber gloves.  
EYE PROTECTION: Safety glasses (ANSI Z-87.1 or equivalent)  
OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Coveralls recommended.  
WORK/HYGIENIC PRACTICES: Where use can result in skin contact, wash exposed areas thoroughly before eating, drinking, smoking, or leaving work area. Launder contaminated clothing before reuse.

=====  
Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES  
-----

BOILING POINT: 212 F (100 C) @ 760mm Hg  
SPECIFIC GRAVITY (H2O = 1): 1.3  
VAPOR PRESSURE (mm Hg): 17 @ 68 F (20 C)  
MELTING POINT: N/A  
VAPOR DENSITY (AIR = 1): N/A  
EVAPORATION RATE (ETHYL ACETATE = 1): >1  
APPEARANCE/ODOR: Gray Paste/Mild Odor  
SOLUBILITY IN WATER: Soluble

=====  
Section 10 -- STABILITY AND REACTIVITY  
-----

STABILITY: Stable  
CONDITIONS TO AVOID: None  
INCOMPATIBILITY (MATERIALS TO AVOID): None known.  
HAZARDOUS DECOMPOSITION PRODUCTS: CO, CO2 and fragmented hydrocarbons.  
HAZARDOUS POLYMERIZATION: Will not occur.

=====  
Section 11 -- TOXICOLOGY INFORMATION  
-----

CHRONIC HEALTH HAZARDS

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.

-----  
TOXICOLOGY DATA

Ingredient Name

-----  
Amorphous Silica

Oral-Rat LD50: 22,500 mg/kg

Inhalation-Rat LC50: N/D

Ketoxime Silane

Oral-Rat LD50: N/D

Inhalation-Rat LC50: N/D

Calcium Carbonate

Oral-Rat LD50: N/D  
Inhalation-Rat LC50: N/D

=====  
Section 12 -- Ecological Information  
-----

ECOLOGICAL DATA

Ingredient Name  
-----

Amorphous Silica

Food Chain Concentration Potential N/D  
WATERFOWL TOXICITY N/D  
BOD N/D  
AQUATIC TOXICITY N/D

Ketoxime Silane

Food Chain Concentration Potential N/D  
WATERFOWL TOXICITY N/D  
BOD N/D  
AQUATIC TOXICITY N/D

Calcium Carbonate

Food Chain Concentration Potential N/D  
WATERFOWL TOXICITY N/D  
BOD N/D  
AQUATIC TOXICITY N/D

=====  
Section 13 -- DISPOSAL CONSIDERATIONS  
-----

Waste Classification: Non-regulated solid waste

Disposal Method: Approved landfill

Waste from this product is not considered hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Dispose of in accordance with Federal, State, and Local regulation regarding pollution.

=====  
Section 14 -- TRANSPORTATION INFORMATION  
-----

DOT: Non-Regulated  
OCEAN (IMDG): Non-Regulated  
AIR (IATA): Non-Regulated  
WHMIS (CANADA): Non-Regulated

=====  
Section 15 -- REGULATORY INFORMATION  
-----

REGULATORY DATA

Ingredient Name  
-----

Amorphous Silica

SARA 313 N/A

TSCA Inventory	Yes
CERCLA RQ	N/A
RCRA Code	N/A
Ketoxime Silane	
SARA 313	N/A
TSCA Inventory	Yes
CERCLA RQ	N/A
RCRA Code	N/A
Calcium Carbonate	
SARA 313	N/A
TSCA Inventory	Yes
CERCLA RQ	N/A
RCRA Code	N/A

=====  
Section 16 -- OTHER INFORMATION  
-----

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). The information herein is given in good faith, but no warranty, expressed or implied is made. Consult RectorSeal for further information: (713) 263-8001