

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURER:	Arro-Mark Company, L.L.C.	24 HOUR EMERGENCY TELEPHONE 201-310-3495
ADDRESS:	158 West Forest Avenue Englewood, NJ 07631 USA	TELEPHONE NO. FOR INFORMATION 888-440-ARRO
TELEPHONE:	(201) 567-4112	DATE PREPARED: APRIL 01, 2014
IDENTITY:	Low Chloride Paint Marker	PRODUCT CLASS: Alcohol based marker
ITEM NO:	MM-08, MM-38, 00108, 00138	OTHER NAMES: Hi Purity,Stainless Steel
COLORS:	XV-12149 Black	BATCH# XV-12586

SECTION 2. COMPOSITION INFORMATION ON INGREDIENTS

Ingredient	CAS No.	OSHA PEL	ACGIH-TLV	Recommended	%
n-Propanol	71-23-8	TWA 200 ppm	TWA 200 ppm	No Data	30-40
Ethanol	64-17-5	1000 ppm	1000 ppm	No Data	10-20
Rosin Based Resin	68152-57-8	TWA 15mg/m3	TWA 10mg/m3	Nuisance dust	10-20
Black Pigment	1333-86-4	TWA 3.5mg/m3	TWA 3.5mg/m3	Nuisance dust	10-20
Isopropyl Alcohol	67-63-0	400 ppm	400 ppm	No Data	0-5

Nuisance dust as free dust only, not as bound in paint or ink.

SECTION 3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW - Black, thin viscosity liquid alcohol odor. Warning! Flammable liquid and vapor. Keep away from heat sparks and flames. May cause eye, skin, and respiratory tract irritation. If swallowed, do not induce vomiting. Get immediate medical attention.

The hi-purity marking pen contains 10 – 13.5 ml of liquid. The liquid contents are only released in a controlled manner when the tip of the pen is pressed. No free liquid is present under normal conditions of use. This product presents only a minimal fire and exposure hazard.

HEALTH HAZARDS

INGESTION: Ingestion of significant amounts is extremely unlikely due to product form. This product has low oral toxicity. Swallowing of the liquid contents may cause irritation, nausea, vomiting and diarrhea. The liquid contents are an aspiration hazard. If swallowed, can enter the lungs and may cause pneumonitis.

EYES: Contact with the liquid contents may be mildly irritating to eyes. May cause redness and tearing.

SKIN: Prolonged and/or repeated contact with the liquid contents may produce mild irritation and defatting with possible dermatitis.

HALATION: Overexposure is very unlikely due to product form. High concentrations may cause nasal and respiratory conditions such as asthma. Intentional abuse may be harmful or fatal.

SECTION 4. FIRST AID MEASURES

INGESTION: Ingestion of significant amounts is extremely unlikely due to product form, however, liquid contents are an aspiration hazard. DO NOT induce vomiting. Call physician.

EYE CONTACT: Flush thoroughly with water. Get medical attention if irritation persists.

SKIN CONTACT: Wash with soap and water. If irritation develops and persists, get medical attention.

INHALATION: Inhalation overexposure is very unlikely due to product form. If irritation is experienced, move to fresh air. Get medical attention if irritation or other symptoms develop and persist.

SECTION 5. FIRE FIGHTING MEASURES

FLASH POINT: 77°F (TCC) ASTM D56

FLAMMABLE LIMITS: LEL 2.1 UEL 13.7

EXTINGUISHING MEDIA: Use water fog, dry chemical, carbon dioxide or foam.

SPECIAL FIRE FIGHTING PROCEDURES: Firefighters should always wear positive pressure self-contained breathing apparatus and full protective clothing.

UNUSUAL FIRE/EXPLOSION HAZARDS: The liquid contents of the pen is a flammable liquid; however, the pen contains a small amount of the liquid, and the contents are released only when pressure is applied to the tip. The product presents only a minimal fire hazard.

SECTION 6. ACCIDENTAL RELEASE MEASURES

SPILL RESPONSE: Large spills of this product are unlikely due to product form. If marking pen leaks, wipe up any free liquid, and place the pen and waste in an appropriate container for disposal. In storage where large numbers of pens may be damaged, eliminate all sources of ignition, ventilate area and collect the pens into a container for disposal. Collect any released liquid with an inert absorbent and place in a container for disposal.

SECTION 7. HANDLING AND STORAGE

HANDLING: Keep product away from open flame. Keep away from children. Replace cap on pen when not in use. Avoid contact with eyes. Avoid prolonged contact with skin.

STORAGE: Store away from heat and flame.

SECTION 8. EXPOSURE CONTROL/PERSONAL PROTECTION

EYE PROTECTION: None should be needed for normal use. Avoid eye contact.

SKIN PROTECTION: None should be needed for normal use. Avoid repeated or prolonged contact with skin.

Wear impervious gloves if needed to prevent possible skin irritation.

RESPIRATORY PROTECTION: None should be needed for normal use.

VENTILATION: No special ventilation is normally required.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Not usually necessary.

WORK/HYGENIC PRACTICES: Follow label instructions.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT:	207 °F	SPECIFIC GRAVITY:	<1 @ 70°F
SOLUBILITY IN WATER:	70% – 80%	MELTING POINT:	No Data
VAPOR PRESSURE:	20.8mm-Hg @ 70°F	EVAPORATION RATE:	1.3
VAPOR DENSITY:	2.1	pH:	Not applicable
APPEARANCE & ODOR:	Black, thin viscosity liquid with alcohol odor.		

SECTION 10. STABILITY AND REACTIVITY

STABILITY: Stable

INCOMPATIBILITY: Strong oxidizing agents. Avoid heat and open flames.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide.

SECTION 11. TOXICOLOGICAL INFORMATION

Please refer to Section 3 for available information on potential health effects.

None of the components of this product are listed as a carcinogen or suspected carcinogen or is considered a reproductive hazard.

SECTION 12. ECOLOGICAL INFORMATION

No data is currently available. Please refer to Section 6 for information regarding accidental releases and Section 15 for regulatory reporting information.

SECTION 13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Discard empty pen in trash. Dispose in accordance with federal, state and local regulations. The liquid contents of the pen meet the definition of hazardous waste under RCRA, D001 (ignitable).

SECTION 14. TRANSPORT INFORMATION

U.S. Hazardous Material Regulation (DOT49CFR): Not regulated per 49 CFR 49 § 173.4 for domestic highway or rail transportation only. Conforms to 49 CFR 173.4a Excepted quantity of Class 3 Flammable liquid.

Canadian Transportation of Dangerous Goods (TDG): Dangerous goods in excepted quantity.

IMDG: Not regulated.

ICAO/IATA: Dangerous goods in excepted quantity.

SECTION 15. STABILITY AND REACTIVITY

U.S. FEDERAL REGULATIONS:

CARCINOGENICITY: NTP: No IARC Monographs: No OSHA Regulations: No

OSHA: Hazardous by definition of Hazard Communications Standard (29 CFR 1910.1200)

SECTION 313 REPORTING REQUIREMENTS: This product does not contain toxic chemicals that are listed and does not require reporting under SARA Title III Sec. 313. TSCA: All compounds are exempt.

INTERNATIONAL REGULATIONS:

CANADIAN WHMIS: Not WHMIS controlled (pens) Bulk: Class B2, D2A

STATE REGULATIONS:

CALIFORNIA PROPOSITION 65: This product is not known to contain any material listed under California's Proposition 65.

SECTION 16. OTHER INFORMATION

HMIS and NFPA Ratings: 2 (Health), 3 (Flammability), 0 (Reactivity), B (Personal Protection) (4=extreme, 3=high, 2=moderate, 1=slight, 0=least) (B=gloves & safety glasses).

This information provided in the Material Safety Data Sheet has been compiled from our experience and data with similar commercially available materials and is believed to be accurate. No guarantee of accuracy is made. It is the user's responsibility to determine the suitability of this information for the adoption of necessary safety precautions and disposal procedures.



Report prepared for:
Arro-Mark Company L.L.C.
 George Pappageorge
 Partner
 158 West Forest Avenue
 Englewood, NJ 07631
 Phone: 201-567-4112
 Fax: 201-567-1373
 Email: arromark@aol.com

Laboratory Report

Report prepared by:
 Salvador Pastor

For further assistance, contact:
 Salvador Pastor
 Technical Manager
 PO Box 51610
 Knoxville, TN 37950-1610
 Phone: 865-546-1335
 Email: tonypickett@galbraith.com

RESULTS OF ANALYSIS
 Sample Number
 Lab ID: 2013-T-4781, 2013-T-4782

	Batch # 12586 High Purity Black XV-12149
Elements	
Aluminum	< 4.53 ppm
Antimony	< 4.53 ppm
Arsenic	< 4.53 ppm
Bismuth	< 4.53 ppm
Boron	< 4.53 ppm
Bromine	< 21 ppm
Cadmium	< 4.53 ppm
Chloride	11 ppm
Chlorine	46 ppm
Copper	< 4.53 ppm
Fluorine	22 ppm
Gallium	< 9.05 ppm
Indium	< 4.53 ppm
Iodine	< 7 ppm
Lead	< 4.53 ppm
Magnesium	< 4.53 ppm
Mercury	<0.0272 ppm
Nitrate	< 7 ppm
Nitrite	< 7 ppm
Phosphorus	< 4.53 ppm
Selenium	< 4.53 ppm
Silver	< 4.53 ppm
Sodium	13 ppm
Sulfur	< 7 ppm
Tellurium	< 4.53 ppm



Report prepared for:
Arro-Mark Company L.L.C.
George Pappageorge
 Partner
 158 West Forest Avenue
 Englewood, NJ 07631
 Phone: 201-567-4112
 Fax: 201-567-1373
 Email: arromark@aol.com

Laboratory Report

Report prepared by:
 Salvador Pastor


For further assistance, contact:
 Salvador Pastor
 Technical Manager
 PO Box 51610
 Knoxville, TN 37950-1610
 Phone: 865-546-1335
 Email: tonypickett@galbraith.com

RESULTS OF ANALYSIS
Sample Number
Lab ID: 2013-T-4781, 2013-T-4782

	Batch # 12586 High Purity Black XV-12149
Elements	
Thallium	< 4.53 ppm
Tin	< 4.53 ppm
Zinc	< 4.53 ppm
Total Halogens as Cl	47 ppm
Water Leachable Chlorides	41 ppm
Water Leachable Fluorides	< 7 ppm
Water Leachable Sulfates	64.5 ppm

Signatures:

- Published by: Salvador Pastor*
- *Physical signatures are on file*
 - *"Published By" signature indicates authorized release of data.*
 - *Analytical Method on file.*



American Association for Laboratory Accreditation

Accredited Laboratory

A2LA has accredited

GALBRAITH LABORATORIES, INC.

Knoxville, TN

for technical competence in the field of

Chemical Testing

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 *General Requirements for the Competence of Testing and Calibration Laboratories*. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated 8 January 2009).

Presented this 25th day of September 2013.


President & CEO

For the Accreditation Council
Certificate Number 2777.01
Valid to July 31, 2015



For the tests to which this accreditation applies, please refer to the laboratory's Chemical Scope of Accreditation.