

**MATERIAL SAFETY DATA SHEET**

---

**Section 1 – Product & Company Identification**

---

Product Name.....: RIDGID Dark Thread Cutting Oil  
Product Catalog No. ....: 41590, 70830, 41610, 41600

Company Name.....: Ridge Tool Company  
Address .....: 400 Clark Street  
: Elyria, Ohio 44036-2023  
Telephone.....: 1-800-519-3456 (USA) (8:00 am – 5:00 pm EST, M-F)  
Emergency Telephone .....: 1-440-323-5581 (USA) (24 Hours)

Issue Date .....: August 16, 2008

---

**Section 2 – Hazards Identification**

---

**EMERGENCY OVERVIEW:**

This product is a liquid that is insoluble in water. Direct eye contact may cause minor, short term irritation. Short term skin exposure is not expected to be irritating. Inhalation and ingestion are not anticipated routes of exposure during normal conditions of use.

**POTENTIAL HEALTH EFFECTS AND SYMPTOMS FROM SHORT TERM / ACUTE EXPOSURE:**

- Eye

This product is not expected to cause eye irritation under normal conditions of use. Symptoms of slight eye irritation may result when direct contact occurs, or when exposed to high mist levels in poorly ventilated areas.

- Skin

Short term skin contact is not expected to cause skin irritation. Prolonged or repeated direct exposure to the skin may result in symptoms of irritation and redness. In severe cases, prolonged or repeated contact may result in dermatitis accompanied by symptoms of irritation, itching, dryness, cracking and/or inflammation.

Product Name.....: RIDGID Dark Thread Cutting Oil

---

- Inhalation:

This product has low volatility and so is not expected to cause respiratory tract irritation during normal conditions of use. Exposure to high mist levels in poorly ventilated areas may cause upper respiratory tract irritation and difficulty breathing.

- Ingestion:

Ingestion may cause slight stomach irritation and discomfort.

- Potential Chronic Health Effects

No further data known.

- Medical Conditions Aggravated By Exposure:

No further data known.

- Carcinogenicity:

This product is not listed as a known or suspected carcinogen by IARC, OSHA or the NTP.

---

### **Section 3 – Composition / Information On Ingredients**

---

Components listed in this section may contribute to the potential hazards associated with exposure to the concentrate. The product may contain additional non-hazardous or trade secret components.

<u>Component:</u>	<u>CAS #</u>	<u>% By Weight</u>
Mineral Oil	64742-54-7	> 90
Sulfur Additive Package	Mixture	< 10

#### **CARCINOGENIC COMPONENTS:**

This product contains no carcinogens.

Product Name.....: RIDGID Dark Thread Cutting Oil

---

---

### Section 4 – First Aid Measures

---

---

#### EYE CONTACT:

Upon direct eye contact, hold eyelids open and flush with a steady, gentle stream of water for at least 15 minutes. If irritation is due to exposure to mist or vapors, remove the individual to fresh air. If irritation persists, flush the eyes with clean water until the irritation subsides. If symptoms persist, contact a physician.

#### SKIN CONTACT:

Remove product from the skin by washing with a mild soap and water. Contaminated clothing should be removed to prevent prolonged exposure. If symptoms of exposure persist, contact a physician.

#### INHALATION:

Inhalation is not an expected route of exposure. If respiratory irritation or distress occurs, remove the employee to fresh air. Contact a physician or other medical professional if irritation or distress persists.

#### INGESTION:

If small amounts are ingested, first aid measures are not likely to be necessary. If larger amounts are ingested or if symptoms of ingestion occur, dilute stomach contents with two glasses of water or milk. (NOTE: Do NOT give anything by mouth to an unconscious person.) Do not induce vomiting without medical supervision. If vomiting occurs spontaneously, keep airway clear. If symptoms of ingestion persist, seek medical attention.

#### NOTE TO PHYSICIANS:

No further data known.

---

---

### Section 5 – Fire Fighting Measures

---

---

#### FIRE AND EXPLOSIVE PROPERTIES:

Flashpoint.....: 385°F Cleveland Open Cup  
Flammability Limits .....: LEL - N/A  
UEL - N/A

Product Name.....: RIDGID Dark Thread Cutting Oil

---

#### EXTINGUISH MEDIA:

In accordance with NFPA guidance, dry chemical, foam or CO2 fire extinguishers are all acceptable. Note that while water fog extinguishers are also acceptable, do NOT apply a direct stream of water onto burning product because it may cause spreading and increase fire intensity.

#### UNUSUAL FIRE AND EXPLOSION HAZARDS:

No further data known.

#### FIRE-FIGHTING PROCEDURES AND EQUIPMENT:

Emergency responders in the danger area should wear bunker gear and self-contained breathing apparatus for fires beyond the incipient stage. See Section 8 of the MSDS for other PPE to be worn as conditions warrant.

---

### **Section 6 – Accidental Release Measures**

---

#### PERSONAL PRECAUTIONS:

Use personal protection recommended in Section 8.

#### ENVIRONMENTAL:

This material is a water pollutant. Do not let spilled or leaking material enter waterways.

#### CLEAN-UP MEASURES:

Important: As with any spill or leak, before responding, ensure that you are familiar with the potential hazards and recommendations of the MSDS. Appropriate personal protective equipment must be worn.

If possible, safely contain the spill with dikes or other spill response equipment appropriate for petroleum or organic material releases. Take measures to prevent spreading of product. Note that while product will ignite, it will not readily burn. However, as a precaution, eliminate ignition sources. Prevent from entering sewers or waterways. Large volumes may be transferred to an appropriate container for proper disposal. Small volumes or residues may be soaked up with absorbents. Spill response materials should be collected for proper disposal.

Product Name.....: RIDGID Dark Thread Cutting Oil

---

---

### Section 7 – Handling And Storage

---

#### HANDLING:

As with any industrial chemical, handle the product in a manner that minimizes exposure to practicable levels. Prior to handling, consult Section 8 of this MSDS to evaluate personal protective equipment needs. Open containers slowly to relieve any pressure. Follow all other standard industrial hygiene practices.

Empty containers may contain product residue. All safety precautions taken when handling this product should also be taken when handling empty drums and containers. Keep containers closed when not in use.

Product residue in empty containers is combustible but will not readily burn. Note, however, that excessive heating or cutting of empty containers may create an ignition source sufficient to start a fire and, in extreme cases, cause an explosion.

#### STORAGE:

Protect product quality by storing indoors and away from extreme temperatures. Close all containers when not in use.

#### SPECIAL COMMENTS:

No further data known.

---

### Section 8 – Exposure Controls / Personal Protection

---

#### EXPOSURE GUIDELINES:

##### Component

---

Mineral Oil	ACGIH TLV:	5 mg / m <sup>3</sup> (as mist)
	ACGIH STEL:	10 mg / m <sup>3</sup> (as mist)
	OSHA PEL:	5 mg / m <sup>3</sup> (as mist)
Sulfur Additive Package	No information	

Product Name.....: RIDGID Dark Thread Cutting Oil

---

#### ENGINEERING CONTROLS:

Normal general ventilation is expected to be adequate. It is recommended that ventilation be designed in all instances to maintain airborne concentrations at lowest practicable levels. Ventilation should, at a minimum, prevent airborne concentrations from exceeding any exposure limits.

The user may wish to refer to 29 CFR 1910.1000(d) (2) and the ACGIH "Threshold Limit Values for Chemical Substances and Physical Agents Biological Exposure Indices" (Appendix C) for the determination of exposure limits of mixtures. An industrial hygienist or similar professional may be consulted to confirm that the calculated exposure limits apply.

#### PERSONAL PROTECTIVE EQUIPMENT:

Selection of personal protective equipment should be based upon the anticipated exposure and made in accordance with OSHA's Personal Protective Equipment Standard found in 29 CFR 1910 Subpart I. The following information may be used to assist in PPE selection.

- Eye Protection

Wear eye protection appropriate to prevent eye exposure. Where splashing is not likely, chemical safety glasses with side shields are recommended. Where splashing may occur, chemical goggles or full face shield is recommended.

- Skin Protection

Gloves are not normally needed during normal conditions of use. If health effects are experienced, oil or chemical resistant gloves such as butyl or nitrile are recommended.

Where splashing or soaking is likely, wear oil or chemical resistant clothing to prevent exposure.

Product Name.....: RIDGID Dark Thread Cutting Oil

---

- Respiratory Protection

A respirator may be worn to reduce exposure to vapors, dust or mist. Select a NIOSH/MSHA approved respirator appropriate for the type and physical character of the airborne material. A self-contained breathing apparatus is recommended in all situations where airborne contaminant concentration has not been confirmed to be below safe levels. Respirator use should comply with the OSHA Respirator Protection Standard found in 29 CFR 1910.134.

- General Hygiene Considerations

Wash thoroughly after handling.

---

### Section 9 – Physical And Chemical Properties

---

Physical Appearance:.....: Black  
Odor. ....: Mild Petroleum  
Physical State.....: Liquid  
Water Solubility.....: Insoluble  
Specific Gravity.....: .878

---

### Section 10 – Stability And Reactivity

---

#### STABILITY:

This product is stable.

#### CONDITIONS TO AVOID:

Avoid contact with incompatible materials and exposure to extreme temperatures.

#### INCOMPATIBLE MATERIALS:

This product is incompatible with strong oxidizing agents.

Product Name.....: RIDGID Dark Thread Cutting Oil

---

**DECOMPOSITION PRODUCTS MAY INCLUDE:**

Thermal decomposition products are dependent on combustion conditions. A complex mixture of airborne solid, liquid, particulates and gasses may evolve when the material burns. Combustion by-products may include:

oxides of carbon

oxides of sulfur

incompletely burned hydrocarbons as fumes and smoke

**POSSIBILITY OF HAZARDOUS REACTIONS:**

This product is not expected to polymerize

---

**Section 11 – Toxicological Information**

---

**EYE EFFECTS:**

No further toxicological data known.

**SKIN EFFECTS:**

No further toxicological data known.

**ORAL EFFECTS:**

No further toxicological data known.

**INHALATION EFFECTS:**

No further toxicological data known.

**OTHER:**

No further toxicological data known.



Product Name.....: RIDGID Dark Thread Cutting Oil

---

---

**Section 12 – Ecological Information**

---

**ECOTOXICOLOGICAL INFORMATION:**

This product has not been evaluated for ecotoxicity. As with any industrial chemical, exposure to the environment should be prevented and minimized wherever possible.

**ENVIRONMENTAL FATE:**

The degree of biodegradability and persistence of this product has not been determined.

---

**Section 13 – Disposal Consideration**

---

**WASTE DISPOSAL:**

Ensure that collection, transport, treatment and disposal of waste product and containers complies with all applicable laws and regulations. Note that use, mixture, processing or contamination of the product may cause the material to be classified as a hazardous waste. It is the responsibility of the product user or owner to determine at the time of disposal whether the product is regulated as a hazardous waste.

---

**Section 14 – Transportation Information**

---

**U.S. DOT HAZARDOUS MATERIAL INFORMATION:**

Not DOT regulated.

Product Name : RIDGID Dark Thread Cutting Oil

---

---

### Section 15 – Regulatory Information

---

#### FEDERAL REGULATIONS:

##### SARA 313:

This product contains NONE of the substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

##### CLEAN WATER ACT:

This product contains mineral oil and is subject to regulation by Section 311 of the Clean Water Act and the Oil Pollution Act. Releases of the product into or leading to surface waters must be reported to the National Response Center at 1-800-424-8802.

##### CERCLA REPORTABLE QUANTITY:

Any components listed below have been assigned a reportable quantity (RQ) by the Federal EPA. Releases of the product into the environment that exceed the RQ for a particular component must be reported to the National Response Center at 1-800-424-8802.

None to report

##### TOXIC SUBSTANCE CONTROL ACT:

The components of this product are listed on the TSCA Inventory.

##### OZONE DEPLETING SUBSTANCES:

This product contains no ozone depleting substances as defined by the Clean Air Act.

##### HAZARDOUS AIR POLLUTANTS:

Any components listed below are defined by the Federal EPA as hazardous air pollutants:

None to report

Product Name : RIDGID Dark Thread Cutting Oil

---

#### STATE REGULATIONS

This product contains mineral oil, and as used, may be regulated by state used oil regulations. Check with the appropriate state agency to determine whether such a regulation exists.

#### CANADA

WHMIS Classification: None

DSL:

The components of this product are listed on DSL Inventory.

---

### Section 16 – Other Information

---

#### HMIS RATING:

Health	Flammability	Reactivity	PPE
1	1	0	X

Prepared by: . . . . . Ridge Tool Company

Issue Date: . . . . . January 5, 2006

Last Revision Date: . . . . . May, 2004

RIDGE TOOL BELIEVES THE STATEMENTS, TECHNICAL INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN ARE RELIABLE BUT THEY ARE GIVEN WITHOUT WARRANTY OR GUARANTEE OF ANY KIND, EXPRESSED OR IMPLIED, AND WE ASSUME NO RESPONSIBILITY FOR ANY LOSS, DAMAGE OR EXPENSE, DIRECT OR CONSEQUENTIAL, ARISING OUT OF THEIR USE.