

## WIRE HOOK ANCHOR

ANCHORAGE CONNECTOR

### FEATURES & BENEFITS

- One of the most lightweight, transportable anchors in the market
- Widely compatible with variety of anchors, including compliant scaffolding, railings, and small I beams.
- Lightweight and durable
- Easy to Install
- Squeeze to open, release to lock
- Ideal for workers who transition between many different locations frequently



**SPRING-LOADED HANDLE**

Squeeze to open anchor. Locks automatically.

**INTEGRATED CONNECTION POINT**

Accommodates a variety of anchors

SHOWN:  
**PART #01860**



# SPECIFICATIONS

## STANDARDS:

OSHA 1926 Subpart M & 1910  
ANSI Z359.18-17 & A10.32-12

Type A Anchorage Connector

## MATERIALS:

Stainless Steel

## WORKER CAPACITY:

130-310 lbs.

## PERFORMANCE:

- Maximum Users: 1
- 5,000 lb. MBS  
(Minimum Breaking Strength)

## NOTES:

- Minimum service temperature: -30°F

PART #	DESCRIPTION	WEIGHT
01860	Wire Hook Anchor	0.9 Lbs

# APPLICATIONS



## PERSONAL FALL ARREST:

Wire Hook Anchors may be used in Personal Fall Arrest applications to support:

- MAXIMUM 1 Personal Fall Arrest System (PFAS). Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs.
- Maximum free fall is 6'.
- Applicable D-rings: Dorsal



## RESTRAINT:

Wire Hook Anchors may be used in Restraint applications. Restraint systems:

- Prevent workers from reaching the leading edge of a fall hazard.
- Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs.
- No free fall is permitted.
- May only be used on surfaces with slopes up to 4/12 (vertical/horizontal).
- Applicable D-rings: Dorsal, Chest, Side, & Shoulder.



**NEED MORE INFORMATION?**

P: 1.800.466.6385 | VISIT OUR WEBSITE: [GUARDIANFALL.COM](http://GUARDIANFALL.COM)