

BASETEK

02-015 **SPECIFICATION SHEET**









ATTRIBUTES:

LINER

13g Blue HDPE A6 **Basetek Liner**

COATING

Black Polyurethane Palm Coating

FEATURES:

• Positive Grip in Dry and Light Oil Environments

APPLICATIONS:

- Automotive Manufacturing
- Metal Stamping
- Steel Handling
- Construction
- Recycling

Armor Guys reference number: 02-015

CATEGORY:

Basetek

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F)





This product can expose you to N,N-Dimethylformamidewhich is known to the State of California to cause cancer. For more information go to www.P65warnings.ca.gov

SPECIFICATIONS

| LINER MATERIALS | 13g Blue HDPE A6 Basetek Liner |
|--------------------------|--------------------------------|
| COATING MATERIALS | Black Polyurethane |
| WRIST DESIGN | Continuous Knit |
| SIZES | XXS-XXL |

| PACKAGING | 1 | | | | | | |
|--------------------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|
| CASE SIZE | XXS | XS | S | М | L | XL | XXL |
| PER CARTON | 12DZ |
| CASE WEIGHT | 23.03/lbs | 24.03/lbs | 24.69/lbs | 26.23/lbs | 27.77/lbs | 30.97/lbs | 33.28/lbs |
| CUFF COLOR | Pink | ■Purple | Red | Yellow | ■Brown | ■Black | Blue |
| ORIGIN | | | | PRC | | | |

PERFORMANCE LEVEL

| EN388: 4X44E | | | | | | | |
|--------------|---|---|---|---|---|---|---|
| ABRASION | 0 | 1 | 2 | 3 | 4 | 5 | X |
| CUT | 0 | 1 | 2 | 3 | 4 | 5 | X |
| TEAR | 0 | 1 | 2 | 3 | 4 | 5 | X |
| PUNCTURE | 0 | 1 | 2 | 3 | 4 | 5 | X |
| CUT TDM TEST | Α | В | С | D | Е | F | |