





#### MORE AIR. MORE WEAR.

Easier breathing and more comfort are what you get when you wear an AirWave respirator. The larger surface area of the patented wave design means more air flows in and out of the mask.

#### 4200 SERIES WITH N95 PROTECTION.

NIOSH approved 95% efficient against solid and liquid particulates, excluding oil based particulates. Use in hot, humid and dusty environments such as welding, soldering and brazing, grinding, sanding, sweeping, bagging, stone quarrying, metal machining, cement, underground mining, polishing, buffing, lime, poultry and textiles. No oils present.

### MORE COMFORT. MORE USE. MORE DURABILITY.

The unique FlexFit<sup>®</sup> design moves with your face for comfort all day long. More comfort means more compliance. The Dura-Mesh<sup>®</sup> shell prevents collapsing from heat and humidity so your mask lasts longer. Longer use means less waste and lower costs.

- Exclusive easy-breathing wave design
- Available in two sizes to fit more workers and increase OSHA compliance
- FlexFit design moves easily with your face and stays in place
- Dura-Mesh shell resists collapsing in heat and humidity
- Straps are securely attached so they don't break at the seal
- Softspun® lining for increased comfort and durability
- Soft foam nose cushion for added comfort
- Meets heat and flame resistance in accordance with ANSI/ISEA 110-2003 Section 7.11.1





# 4200 N95

## PARTICULATE RESPIRATOR

#### USE AGAINST:

1. Particulate aerosols free of oil.

#### DO NOT USE AGAINST:

- 1. Concentrations of contaminants which are unknown, or are immediately dangerous to life or health.
- 2. Concentrations of particulates which exceed the maximum use concentration or 10 times the OSHA Permissible Exposure Limit, whichever is lower.
- 3. Gases, vapors, asbestos, paint spray, sandblasting or particulate materials which generate harmful vapors.
- 4. Oil-based mists.

#### RESTRICTIONS

- 1. This respirator does not supply oxygen and must not be used in atmospheres containing less than 19.5% oxygen.
- 2. Do not remain in contaminated area if any physical distress occurs, for example breathing difficulty, dizziness or nausea.
- 3. Leave contaminated area and replace respirator if it is damaged, distorted, a proper fit can not be obtained or breathing becomes difficult.
- 4. Prior to each use, carefully inspect the entire respirator, including filter media and strap/weld attachment area for tears and damage. Staple or strap/weld attachment perforations do not affect respirator performance.
- 5. Do not alter, modify, or abuse this respirator.
- 6. Store unused respirators in box/bag in a clean, dry, non-contaminated area.
- 7. Dispose of respirator according to your employer's policy and local regulations.
- 8. Dispose no later than thirty days after first use.
- 9. Use respirator before the "use by" expiration date printed on box/bag.
- 10. If used for welding, wear appropriate eye and face protection.

#### WARNINGS TO USER

- 1. Follow all instructions and warnings on the use of this respirator and wear during all times of exposure. Failure to do so will reduce respirator effectiveness, wearer protection and may result in sickness or death.
- 2. Before use, the user must first be trained by the employer in proper respirator use, in accordance with applicable safety and health standards, for the contaminant and exposure level in the assigned work area.
- 3. The particulates and other contaminants which can be dangerous to your health include those which you cannot see, taste, or smell.
- 4. This product has not been sold with warnings or use instructions for personnel involved in healthcare or related situations, where there may be the possibility of contact with disease or biological hazards. If you are considering such uses, first call the Moldex Technical Service Dept., +1 (310) 837-6500 ext. 512/550 or +1 (800) 421-0668 ext. 512/550.

Moldex-Metric. Inc. CULVER CITY, CALIFORNIA, U.S.A. +1 (800) 421-0668 SE RESPIRATORS ARE APPROVED ONLY IN THE FOLLOWING CONFIGURATIONS PROTECTION<sup>1</sup> RESPIRATOR CAUTIONS AND LIMITATIONS<sup>2</sup> TC-4200 4201 844-5396 ABCJMNOF N95 84A-5397 ABCUMNOR N95 1. Protection N95 Particulate Filter (95% filter efficiency level) effective against particulate aerosols free of oil; time use restrictions may apply 2. Cautions and Limitations 2. Catiforts and Limitations
A Not for use in atmospheres containing less than 19.5 percent oxygen.
B- Not for use in atmospheres immediately dangerous to life or health.
C- Do not exceed maximum use concentrations established by regulatory standards.
J- Failure to properly use and maintain this product could result in injury or death.
M- All approved respirators shall be selected, fitted, used, and maintained in accordance with MSHA, OSHA, and other applicable regulations.
N. Never substitute, modify, add, or omit parts. Use only exact replacement parts in the configurations as specified by the manufacturer

- manufacturer
- re to user's instructions, and/or maintenance manuals for information on use and maintenance of these respirators. NIOSH does not evaluate respirators as surgical masks

#### Packaging

Part #	Description	Quantity	Case
4200	Medium/Large N95 Airwave Disposable Respirator	10 per Box	8 Boxes
4201	Small N95 Airwave Disposable Respirator	10 per Box	8 Boxes

#### LIMITED WARRANTY - IMPORTANT NOTICE TO PURCHASER This limited warranty is made in lieu of the warranties of merchantability, fitness for particular purposes and all other warranties, express or implied.

There are no other warranties which extend beyond the description on the face hereof. The physical standards and specifications of Moldex will be met by products sold. Exclusive Remedies: damages for the breach of this limited warranty are limited to the replacement of such quantity of Moldex products proved to be defectively manufactured. Except as provided above. Moldex shall not be liable or responsible for any loss, damages, or liability, direct, indirect, incidental, special or consequential, arising out of a sale, use or misuse, or the inability to use products by the user.

**DISTRIBUTED BY:** 



#### **MOLDEX-METRIC, INC.**

10111 West Jefferson Blvd. Culver City, CA 90232 TEL: +1 (800) 421-0668 or +1 (310) 837-6500 FAX: +1 (310) 837-9563 E-mail: sales@moldex.com www.moldex.com

#### **MOLDEX TECHNICAL SERVICE DEPARTMENT:**

+1 (800) 421-0668 or +1 (310) 837-6500 ext. 512/550 **CANADIAN CUSTOMER SERVICE** Tel: +1 (800) 421-0668, Ext. 517 Fax: +1 (310) 837-9563



MOLDEX

GISTERE

