



# SPECIFICATION SHEET

## 56-424



### HI-PERFORMANCE NITRILE BY ATG®

- MaxiDry® by ATG®, ultra lightweight nitrile on fine gauge seamless knit nylon liner, black palm & fingertip coated, non-slip grip, 10 inch length
- Ultra thin design provides excellent comfort and flexibility along with maximum finger tip tactile sensitivity
- Exclusive GripTech® coating offers non-slip capabilities
- Locking cuff ensures the glove doesn't slip on the hand
- LiquiTech® Barrier Technology provides resistant to oils & liquids
- Silicone free

### APPLICATIONS

- Precision handling in oily and wet environments
- Engine, power train, gear box, transmission, shock absorber assembly
- Handling small castings, small components, and parts
- General handling and maintenance

### CARE INSTRUCTIONS

Use commercial laundry soap or detergent (do NOT use dry cleaning solutions) Wash in warm to medium hot water, do not exceed 104°F (40° C). Wash for 10 minutes and rinse in cold water. Repeat wash and rinse if soiling is especially heavy. Tumble dry - maximum temperature 140°F (60° C).

### TECHNICAL DATA

MATERIAL	Nitrile, nylon, Lycra®				
COLOR	■ Purple / ■ Black				
CUFF STYLE	Continuous knit				
SIZES	S - XXL				
PACKAGING	12 pairs per dozen, 6 dozen per case				
CASE	20.0" x 11.8" x 10.8" / 50.8cm x 30.0cm x 27.4cm				
CASE WEIGHT (S-XXL)	S	M	L	XL	XXL
	15.4 lbs 7.0 kg	16.5 lbs 7.5 kg	17.6 lbs 8.0 kg	18.7 lbs 8.5 kg	19.8 lbs 9.0 kg
COO	Sri Lanka				
HARM CODE	6116.10.6500				

### PERFORMANCE PROPERTIES

EN388: 4121						
ABRASION	0	1	2	3	4	-
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	-
PUNCTURE	0	1	2	3	4	-

### BARCODES

ITEM	BAG	DOZEN	CASE
■ 56-424/S	---	01616314117038	02616314117037
■ 56-424/M	---	01616314117021	02616314117020
■ 56-424/L	---	01616314117014	02616314117013
■ 56-424/XL	---	01616314117045	02616314117044
■ 56-424/XXL	---	01616314117052	02616314117051



### DIMENSIONS (in/cm)

	S	M	L	XL	XXL
<b>A</b>	9.8 / 25.0	9.8 / 25.0	9.8 / 25.0	9.8 / 25.0	9.8 / 25.0
<b>B</b>	3.2 / 8.2	3.3 / 8.4	3.7 / 9.4	3.8 / 9.7	3.9 / 10.0

Thickness: 1.3mm

