

SPECIFICATIONS

Product Description: **DUCTING,**
Part Number: **9500-06, 9500-15, 9500-25**
Style: **8" (20.3 cm) RETRACTABLE**

GENERAL DESCRIPTION:

This product is lightweight, retractable, and designed for maximum air handling capabilities. Dual direction flow with minimum friction loss.



CONSTRUCTION:

- Vinyl and polyester materials
- Single-Ply
- PVC-coated
- Temperature Range: -20° F to 180° F (-28.8° C to 82.22° C)
- Retractable, non-collapsible design
- Class 1 hard drawn spring steel wire helix
- Meets ASTM 227 specs
- Meets flame retardant requirements of UL94V-0
- Yellow color with black weather-strip
- Fastening cuffs at both ends

AVAILABLE:

Part No.	Diameter	Length	End-Straps
9500-06	8" (20.3 cm)	6' (1.82 m)	Dual
9500-15	8" (20.3 cm)	15' (4.57 m)	Dual
9500-25	8" (20.3 cm)	25' (7.62 m)	Dual

ACCESSORIES:

Part No.	Diameter	Description
9500-01	8" (20.3 cm)	Duct to Duct Connector with raised lip
9510-50	8" (20.3 cm)	Manhole Ventilation Passthru
9500-35	8" (20.3 cm)	Storage Rack for 8" (20.3 cm) Ducting (up to 25' (7.62 m) in length)
9500-45	8" (20.3 cm)	Storage Bag