

## KFM 15-10 F (601752620) Bevelling tool **Metal Carry Case**

Order no. 601752620 EAN 4007430298409



Representative picture









- Metal Bevelling tool for chamfer heights up to 10 mm for weld seam preparation
- One-touch controller: Patented, tool-free setting of the cutting depth in 0.1" steps; stop points for short setting times, and protection against unintentional adjustment of the cutting depth when working
- Precise setting of chamfer angle directly using the guide plate
- Universal carbide burr with three carbide inserts for all chamfer angles from 0-90°
- Controlled work with large-surface guide plates
- Stop roller to guide along pipes for easy weld seam preparation
- Bail handle adjusts without tools for secure, even guiding
- Metabo Long-life motor with patented dust protection for long service life
- Tacho-Constamatic (TC)-Full Wave Electronics: fast work progress by means of constant speed under load
- Electronic overload protection, soft start and restart protection
- Protection for users with metal sheet sides to deflect chips

www.metabo.com 1/2



Technical values	
Parameters	
No-load speed	12500 RPM
Amps	13 AMPS
Rated input power	1500 W
Output power	810 W
Type of edges	Chamfer
Max. chamfer width 45°	9/16 "
Max. chamfer height at 45°	3/8 "
Grade cutting depth setting	0.00394 "
Curvature smallest exterior Ø	2 15/16 "
Weight (without power cable)	10.8 lbs
Cable length	13 ft
Noise emission	
Sound pressure level	92 dB(A)
Sound power level (LwA)	103 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

3 Carbide indexable inserts universal

Stopper roller

Screwdriver for Torx screws 15

Screwdriver SW 4 with T-handle

Open-Ended Spanner SW 10

Bow type handle

Metal carrying case

www.metabo.com 2 / 2