

**L.B.WHITE****TRADESMAN® KEROSENE
FORCED AIR HEATERS**

TRADESMAN® K	K75	K125	K175	K210	K400	K650
BTU/H RATING	75,000	125,000	175,000	210,000	400,000	650,000
HEATED AIR OUTPUT (CFM)	265	520	600	650	1,400	3,600
FUEL TYPE	KEROSENE*	KEROSENE*	KEROSENE*	KEROSENE*	KEROSENE*	KEROSENE*
FUEL CONSUMPTION MAX. (GAL./HR.)	0.6	0.95	1.3	1.6	3.0	4.9
TANK CAPACITY	5	10	13	13	29	50
OPERATING TIME MAX. (HRS.)	8.3	10.5	10.0	8.0	9.5	10.0
AMPS (CONTINUOUS OPERATION)	1.6	2.5	3.2	3.7	4.4	7.1
PUMP PRESSURE (PSI)	3.8	5.5	6.5	8.5	125	110
MOTOR HORSEPOWER	1/8	1/5	1/4	1/3	1/2	3/4
LENGTH (IN.)	32	36.1	41.8	41.8	52.5	69.2
WIDTH (IN.)	11.8	21.5	23.1	23.1	31.4	32.8
HEIGHT (IN.)	16.8	24.6	26.1	26.1	32.8	48.7
SHIPPING WEIGHT (LBS.)	32.0	63.7	71.6	73.2	163.0	298.0
THERMOSTAT	S	S	S	S	S	S
HANDLE(S)	S	S	S	S	S	S
WHEELS	-	NO FLAT	NO FLAT	NO FLAT	NO FLAT	NO FLAT
FUEL & PUMP PRESSURE GAUGES	S / S	S / S	S / S	S / S	S / -	S / -
ON/OFF SWITCH	S	S	S	S	S	S
CORD CADDY	S	S	S	S	S	-
U.S./CANADA CERTIFICATION	YES	YES	YES	YES	YES	YES
S=Standard	TWO YEAR WARRANTY					

* Kerosene, #1 and #2 Diesel or #1 Fuel Oil



CA RESIDENTS:

**WARNING**Cancer and reproductive harm. See
www.P65Warnings.ca.gov.**WORLD PROVIDER OF INNOVATIVE HEATING SOLUTIONS**411 Mason Street, Onalaska, WI 54650
(800) 345 7200
(608) 783 5691
(608) 783 6115, fax
www.lbwhite.com© 2017 L.B. White Co.
All rights reserved.
All specifications are subject
to change without notice.